

The new SXV and RXV are living proof of Aprilia's core design philosophy—design racebikes and introduce competition technology directly to consumer motorcycles. The SXV and RXV are the first truly modern multi-cylinder off-road machines, are available in a 450cc or 550cc versions. Coming to the US as 2007 models, these machines redefine smooth performance, attention to detail, and are be the most unique machines on the market. Totally uncompromising, these machines are designed with just one thing in mind—winning.

COLORS

SXV 4.5/SXV 5.5



Supermoto Edition

RXV 4.5/RXV 5.5



Enduro Edition

ENGINE TYPE	SXV 4.5/SXV 5.5 77° V twin four-stroke, liquid cooled; single overhead cam with rocker operated exhaust valves, chain timing drive, four-valve heads, titanium valves
DISPLACEMENT	449cc • 549cc
BORE X STROKE	3" x 1.9" (76 x 49.5 mm) • 3.1" x 2.2" (80 x 55 mm)
COMPRESSION RATIO	12.5:1 • 12:1
FUEL SYSTEM	Integrated engine management system controlling ignition and fuel injection; throttle body
PRIMARY DRIVE	Spur gears, transmission ratio: 22/56
FINAL DRIVE	Chain, transmission ratio: 15/46 • 16/46
FRAME	Steel perimeter frame with alloy vertical members
FRONT SUSPENSION	48 mm upside down fork, double adjustment
REAR SUSPENSION	Box section aluminum swingarm with cast body; hydraulic monoshock with compression and rebound adjustment
FRONT BRAKE	320 mm stainless steel disc with radial caliper
REAR BRAKE	240 mm stainless steel disc with floating caliper
WHEELS	Light alloy, front: 3.5 x 17" rear: 5.5 x 17"
FRONT TIRE/REAR TIRE	120/70 x 17" / 180/55 x 17"
LENGTH/WIDTH	87.4" (2,220 mm) / 31.5" (800 mm)
GROUND CLEARANCE	12.5" (318 mm)
SEAT HEIGHT	36.1" (918 mm)
TANK CAPACITY	2.1 gallons (7.8 liters)
DRY WEIGHT	275.5 lbs (125 kg)
AVAILABLE COLOR	Black
MSRP	\$8,199 • \$8,399

ENGINE TYPE	RXV 4.5/RXV 5.5 77° V twin four-stroke, liquid cooled; single overhead cam with rocker operated exhaust valves, chain timing drive, four-valve heads, titanium valves
DISPLACEMENT	449cc • 549cc
BORE X STROKE	3" x 1.9" (76 x 49.5 mm) • 3.1" x 2.2" (80 x 55 mm)
COMPRESSION RATIO	12.5:1 • 12:1
FUEL SYSTEM	Integrated engine management system controlling ignition and fuel injection; throttle body
PRIMARY DRIVE	Spur gears, transmission ratio: 22/56
FINAL DRIVE	Chain, transmission ratio: 15/48
FRAME	Steel perimeter frame with alloy vertical members
FRONT SUSPENSION	45 mm upside down fork, double adjustment
REAR SUSPENSION	Box section aluminum swingarm with cast body; hydraulic monoshock with compression and rebound adjustment
FRONT BRAKE	270 mm stainless steel disc with floating caliper
REAR BRAKE	240 mm stainless steel disc with floating caliper
WHEELS	Light alloy, front: 1.6 x 21" rear: 2.15 x 18"
FRONT TIRE/REAR TIRE	90/90 x 21" / 140/80 x 18"
LENGTH/WIDTH	87.5" (2,222 mm) / 31.5" (800 mm)
GROUND CLEARANCE	15.6" (396 mm)
SEAT HEIGHT	39.2" (996 mm)
TANK CAPACITY	2.1 gallons (7.8 liters)
DRY WEIGHT	262.3 lbs (119 kg)
AVAILABLE COLOR	Black
MSRP	\$8,199 • \$8,399

* The 550cc engine specifications are highlighted in Red

www.apriliausa.com www.aprilia-offroad.com

APRILIA USA 140 EAST 45TH STREET, 17TH FLOOR, NEW YORK, NY 10017

©2006 Aprilia USA. Technical specifications and colors are subject to change without notice. Not all colors are available in all regions. Contact your local dealer for specific availability.